

REMARKS

Reconsideration and allowance are respectfully requested. Claims 7-9, 12 and 15 are currently pending. Claims 5, 6, 9-11, 13 and 14 were rejected. Applicants thank the Examiner for indicating that Claims 7, 8, 12 and 15 would be allowable if rewritten in independent form. In response, Claims 5, 6, 10, 11, 13 and 14 have been cancelled and Claims 7 and 12 have been amended into independent form. Additionally, Claims 8 and 15 have been amended for clarity, and Claim 9 has been amended to depend from Claim 7, as well as amended for clarity.

A revised version of Figure 1 has also been submitted. The revision adds the label "Prior Art" to the Figure. No new matter has been entered.

All objections and rejections having been addressed, it is respectfully submitted that the present application is in condition for allowance, and a Notice to that effect is earnestly solicited.

Respectfully submitted,

  
Terryence F. Chapman

TFC/T/cc

FLYNN, THIEL, BOUTELL	Dale H. Thiel	Reg. No. 24 323
& TANIS, P.C.	David G. Boutell	Reg. No. 25 072
2026 Rambling Road	Ronald J. Tanis	Reg. No. 22 724
Kalamazoo, MI 49008-1631	Terryence F. Chapman	Reg. No. 32 549
Phone: (269) 381-1156	Mark L. Maki	Reg. No. 36 589
Fax: (269) 381-5465	David S. Goldenberg	Reg. No. 31 257
	Liane L. Churney	Reg. No. 40 694
	Brian R. Tumm	Reg. No. 36 328
	Steven R. Thiel	Reg. No. 53 685
	Sidney B. Williams, Jr.	Reg. No. 24 949

Encl: Replacement Specification  
Marked-up Specification  
Revised Figure 1  
Postal Card

136.0703

SPECIFICATION

CONTOUR EMPHASIZING CIRCUIT

TECHNICAL FIELD

[0001] The present invention relates to a contour emphasizing circuit designed for sampling a contour component from an input video signal (e.g., a digital input video signal), multiplying the sampled contour component by a coefficient (one of coefficients including 1) for contour emphasis, and adding the product thereof to the input video signal for a outputting contour-emphasized video signal.

BACKGROUND OF THE INVENTION

[0002] The PDP (Plasma Display Panel) equipment using the plasma display panel and LCD (Liquid Crystal Display) equipment using the liquid crystal display panel as thin and lightweight display equipment have come to attract public attention. Such display equipment is conventionally of the direct-drive type using a digital video signal, wherein a contour emphasizing circuit, such as ~~one~~ shown in Fig. 1, is used for obtaining the contour-emphasized video signal from the input video signal.

[0003] The contour emphasizing circuit shown in Fig. 1 comprises a contour pick-up unit 10, a delay adjusting unit 12 and adder 14.

[0004] The contour pick-up unit 10 comprises one-dot delay units 18, 20 for sequentially delaying by one-dot the digital luminance signals (an example of a video signal), ~~which has~~ have been input to the input terminal

16, an adder 22 for adding the luminance signal Y input to the input terminal 16 to the output signal from the one-dot terminal ~~16~~ 20 to obtain the sum, a multiplier ~~26~~ 24 for multiplying the sum by coefficient  $1/4$  for outputting the product thereof, a multiplier 26 for multiplying the output signal from the one-dot delay unit 18 by coefficient  $1/2$  for outputting the product thereof, and a subtracter 28 for subtracting the output signal of the multiplier 24 from the output signal of the multiplier 26; wherein the contour component (i.e., high-pass component) HE in a horizontal direction of the reference picture element are sampled, for output, from the picture elements on the left side and right side (preceding and subsequent picture elements on time basis) of the reference picture element.

[0005] A delay adjusting unit 12 is designed ~~for adjusting to adjust~~ the timing ~~for the input~~ of the luminance signal, ~~which has been input~~ as provided to the input terminal 16 and passed on, to the adder 14, to the timing ~~for the input~~ of the contour component HE as, ~~which has been~~ sampled by contour pick-up unit 10 and passed on, to the adder 14. The delay adjusting unit 12 coordinates the timing of the luminance signal Y to the contour component HE by delaying the output of luminance signal Y, which has been input to the input terminal 16, for a predetermined time interval.

[0006] The adder 14 adds the luminance signal Y, which is output from the delay adjusting unit 12, to the contour component HE, which is sampled by the contour pick-up unit 10, to output generate the sum (Y + HE) representing, as a contour-emphasized luminance signal component, to an output terminal 30.

[0007] However, the contour emphasizing circuit shown in Fig. 1 ~~has~~ suffers from a problem, as is further

January 6, 2004

described below, in that its design allows ~~because of being designed so that~~ the contour component HE sampled by the contour pick-up unit 10 is to be directly output to the adder 14 regardless of ~~the luminance level of the~~ whether a high or low level of luminance signal Y is input to the input terminal 16 ~~is high or low~~.

[0008] As a result of the above ~~The problem, an is~~ that unnatural picture having overemphasized contour ~~is~~ can be produced if a contour component having too high a value is added to a relatively dark picture of a low luminance level. Another problem of the circuit is that the contour cannot be emphasized sufficiently if a contour component having too low a value is added to a bright picture having a high luminance level.

[0009] The present invention is designed for the purposes of solving the above problems and for providing a contour emphasizing circuit capable of accomplishing a level of contour emphasis ~~matching that matches~~ the luminance level of input video signal.

#### DISCLOSURE OF THE INVENTION

[0010] The contour emphasizing circuit according to the present invention is characterized by comprising a contour pick-up unit for sampling a contour component from an input video signal, a luminance level judging unit for discriminating the luminance level of the input video signal, a coefficient control unit for not only selectively changing coefficient among a plurality of coefficients according to the judging signal from the luminance level judging unit but also multiplying the contour component sampled by means of a contour pick-up unit by a selected coefficient for the outputting the product thereof and an adder for adding the contour

component output from the coefficient control unit to the input video signal for outputting a contour-emphasized video signal.

[0011] A coefficient is selected from among a plurality of coefficients, so that a plurality of coefficients are available for being multiplied by the contour component according to the luminance level of the input video signal. Thus, the picture can be prevented from becoming an unnatural picture by controlling the contour component to be added to the input video signal to a value matching the luminance level of the input video signal.

[0012] Further, the level judging unit may comprise a decoder for discriminating the luminance level of the input video signal from among n number (n = 2 and larger integers) of luminance levels, and the coefficient control unit may comprise n number of multipliers for multiplying the contour component, which is sampled by means of the contour pick-up unit, by the coefficient corresponding to each luminance level among n number of luminance levels for outputting the product thereof, n number of AND gates using, as the gate control signal, the signal interpreted by the decoders connected respectively to the output sides of the n number of multipliers and an OR gate connected to the output sides of the n number of the AND gates. By doing so, the level judging unit and the coefficient control unit can be formed easily.

[0013] Further, the level judging unit may comprise a decoder capable of discriminating each of 4 luminance levels of an input video signal, and the coefficient control unit may comprise 4 multipliers for multiplying the contour component, which is sampled by the contour pick-up unit, by one of the coefficients  $1/8$ ,  $1/4$ ,  $1/2$

January 6, 2004

and 1 for outputting the product thereof, 4 AND gates respectively connected to the output sides of the 4 multipliers for using, as the gate control signal, the signal interpreted by the decoders respectively connected, and an OR gate connected to the output side of the 4 AND gates. By doing so, the level judging unit and the coefficient control unit can be formed more easily.

[0014] Further, the composition of the contour pick-up unit can be simplified by composing the contour pick-up unit with a horizontal contour component pick-up unit designed for sampling the contour component in the horizontal direction from input video signal.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Fig. 1 is a block diagram showing an example of a conventional contour emphasizing circuit.

[0016] Fig. 2 is a block diagram showing an embodiment of the contour emphasizing circuit according to the present invention.

[0017] Fig. 3 is a block diagram showing examples of the level judging unit and the coefficient control unit shown in Fig. 2.

#### BEST MODES FOR CARRYING OUT THE PRESENT INVENTION

[0018] The content of the present invention will be described in detail referring to the accompanying drawings.

[0019] Fig. 2 shows a contour emphasizing circuit ~~as~~ according to an embodiment of the present invention, wherein common reference numerals are assigned to those parts common to those shown in Fig. 1.

[0020] In Fig. 2, numeral 10 denotes the contour pick-up unit; 12,13, the delay adjusting unit; 14, an adder; 15, the level judging unit; 17, coefficient control unit.

[0021] The contour pick-up unit 10 comprises one-dot delay units 18, 20 for sequentially delaying by 1 dot the digital luminance signals (an example of a video signal), ~~which has~~ have been input to the input terminal 16, an adder 22 for adding the luminance signal Y input to the input terminal 16 to the output signal from the one-dot terminal ~~16~~ 20 to obtain the sum, a multiplier ~~26~~ 24 for multiplying the sum by coefficient  $1/4$  and for outputting the product thereof, and a subtracter 28 for subtracting the output signal of the multiplier 24 from the output signal of the multiplier 26; wherein the contour components HE in the horizontal direction are sampled, for output, from the picture elements on the left side and right side of the reference picture element.

[0022] The level judging unit 15 is designed to discriminate the luminance level of the luminance signal Y input to said input terminal 16 and output a corresponding judging signal. More specifically, as shown in Fig. 3, (the level judging unit 15) comprises the decoder 32 for decoding the luminance level of the luminance signal Y with reference to the values of the upper 3 bits of the 8-bit luminance signal Y. That is, the decoder 32 outputs a signal (e.g., H-level signal) corresponding to the output sides ①, ②, ③ and ④ depending on whether the values of the upper 3 bits of the luminance signal Y input to the input terminal 16 correspond to ~~which of either~~ [000], [001], [010~011] and [100~111]. Consequently, the decoder 32 determines ~~thereby interpreting whether~~ the luminance level of the luminance signal Y corresponds to ~~which one of the~~ 4

levels of hexadecimal numbers of 4 levels, namely,  
[00~1F], [20~3F], [40~7F] and [80~FF].

[0023] The coefficient control unit 17 is designed ~~for~~  
to selectively changing change the coefficient according  
~~to the~~ a judging signal output from generated by the  
level judging unit 15 and delivered by way of the delay  
adjusting unit 13, as well as for multiplying the contour  
component sampled by means of the contour pick-up unit 10  
by this coefficient, and for outputting the product  
thereof. More specifically, as shown in Fig. 3, ~~(the~~  
coefficient control unit 17) ~~comprises the four~~  
multipliers 36<sub>1</sub>, 36<sub>2</sub>, 36<sub>3</sub> and 36<sub>4</sub> ~~for that~~ selectively  
multiplying multiply the contour component HE, ~~which has~~  
~~been sampled by said contour pick up unit 10 and input by~~  
~~way of the input terminal 34,~~ by the coefficients 1/8,  
1/4, 1/2 and 1, respectively, and then feed into for  
~~outputting of the product thereof,~~ four AND gates, 38<sub>1</sub>,  
38<sub>2</sub>, 38<sub>3</sub> and 38<sub>4</sub>, respectively. Each of the AND gates,  
38<sub>1</sub>, 38<sub>2</sub>, 38<sub>3</sub> and 38<sub>4</sub>, connects to one of the outputs of  
the decoder 32, thereby allowing connected to the output  
~~sides of the four multipliers 36<sub>1</sub>, 36<sub>2</sub>, 36<sub>3</sub> and 36<sub>4</sub> for~~  
~~using the signal decoded by the decoder 32 to be used as~~  
a gate control signal. An, and the OR gate 40 connected  
connects to the output sides of the four AND gates, 38<sub>1</sub>,  
38<sub>2</sub>, 38<sub>3</sub> and 38<sub>4</sub>; wherein the contour component is output  
to the adder 14 from the OR gate by way of the output  
terminal 42. It should be noted that in order to  
simplify the illustration of Fig. 3, Further, in Fig. 3,  
~~for the simplicity of illustration,~~ the delay adjusting  
unit 13 interposed between the decoder 32 and the  
coefficient control unit 17 ~~is~~ has been omitted, as the  
result, ~~in the diagram,~~ the output terminals ①, ②, ③



January 6, 2004

and ④ in the diagram are shown as if the signals were directly input to the AND gates 38<sub>1</sub>, 38<sub>2</sub>, 38<sub>3</sub> and 38<sub>4</sub>.

[0024] The delay adjusting unit 13 delays ~~for a predetermined time interval the output of the judging signal generated by from the level judging unit 15 for a predetermined time interval~~ in order to respectively adjust the timing of the judging signal output ~~for outputting to the coefficient control unit 17, as well as the contour component HE sampled from the input luminance signal by the contour pick-up unit 10 and the timing for inputting to the coefficient control unit 17 the judging signal from the level judging unit 15.~~

[0025] The adder 14 adds the luminance signal Y, which has been input to the input terminal 16 and delayed for a predetermined time interval by the delay adjusting unit 12, to the contour component output from the coefficient control unit 17. The sum of the luminance signal Y and contour component output is then provided ~~for outputting the sum to the output terminal 30 as a contour-emphasized luminance signal.~~

[0026] The delay adjusting unit 12 delays the output of the luminance signal Y, which has been input to the input terminal 16, for a predetermined time interval in order ~~oder~~ to respectively adjust the timing for the input of the luminance signal, ~~which has been input to the input terminal 16, to the adder 14 for combining with and the timing for the input of the contour component, which has been output from the coefficient control unit 17, to the adder 14.~~

[0027] Next, the functions of the parts shown in Fig. 2 will be explained referring with reference to Fig. 3 too.

January 6, 2004

[0028] (1) The contour component HE is sampled from the 8-bit luminance signal, which has been input to the input terminal 16, by the contour pick-up unit 10. The, ~~and the~~ sampled contour component HE is then input to the coefficient control unit 17.

[0029] (2) In Fig. 3, the decoder 32 and the coefficient control unit 17 respectively function as described in (a), (b), (c) and (d) below depending on whether the luminance level of the 8-bit signal ~~input to~~ provided at the input terminal 16 corresponds to ~~which~~ one of the four levels, i.e., [00~1F] (hexadecimal number; the same applies hereinafter), [20~3F], [40~7F] and [80~FF].

[0030] (a) Case where the luminance level of luminance signal Y is [00~1F]:

[0031] The decoder 32 interprets that the luminance level is [00~1F] on the basis ~~of~~ that the values of the upper 3 bits of the luminance signal Y is [000], ~~thereby outputting~~ and subsequently outputs an H-level signal from output side ①. This output signal is delayed for a predetermined time interval by the delay adjusting unit 13 (not shown in Fig. 3) and then input to the AND gate 38<sub>1</sub> for the electrification (i.e., being kept open) thereof. In this condition, L-level signals are output from the output sides ② through ④ of the decoder 32, so that other AND gates 38<sub>2</sub> through 38<sub>4</sub> are kept unelectrified (i.e., being kept closed).

[0032] When the AND gate 38<sub>1</sub> is electrified, the contour component (HE/8) multiplied by 1/8 by means of the multiplier 36<sub>1</sub> is input to the adder 14 by way of the AND gate 38<sub>1</sub>, OR gate 40 and output terminal 42.

[0033] (b) Case where the luminance level of luminance signal Y is [20~3F]:

January 6, 2004

[0034] The decoder 32 interprets that the luminance level is [20~3F] on the basis ~~of~~ that the values of the upper 3 bits of the luminance signal Y are [001] and outputs an H-level signal from the output side ②. This output signal is delayed for a predetermined time interval by means of the delay adjusting unit 13 and then input to the AND gate 38<sub>2</sub> for the electrification thereof.

[0035] When the AND gate 38<sub>2</sub> is electrified, the contour component (HE/4), which has been multiplied by 1/4 by multiplier 36<sub>2</sub>, is input to the adder 14 by way of the AND gate 38<sub>2</sub>, OR gate 40 and output terminal 42.

[0036] (c) Case where the luminance level of luminance signal Y is [40~7F]:

[0037] The decoder 32 interprets that the luminance level is [40~7F] on the basis ~~of~~ that the values of the upper 3 bits are [010~011] and outputs an H-level signal from the output side ③. This output signal is delayed for a predetermined time interval by means of the delay adjusting unit 13 and then input to the AND gate 38<sub>3</sub> for the electrification thereof.

[0038] When the AND gate 38<sub>3</sub> is electrified, the contour component (HE/2) multiplied by 1/2 by means of the multiplier 36<sub>3</sub> is input to the adder 14 through the AND gate 38<sub>3</sub>, OR gate 40 and output terminal 42.

[0039] (d) Case where the luminance level of luminance signal Y is [40~7F]:

[0040] The decoder 32 interprets that the luminance level is [40~7F] on the basis ~~of~~ that the values of the upper 3 bits are [010~011] and outputs an H-level signal from the output side ④. This output signal is delayed for a predetermined time interval by means of the delay adjusting unit 13 and then input to the AND gate 38<sub>4</sub> for the electrification thereof.

[0041] When the AND gate 38<sub>4</sub> is electrified, the contour component (HE) multiplied by 1 by means of the multiplier 36<sub>4</sub> is input to the adder 14 through the AND gate 38<sub>4</sub>, OR gate 40 and output terminal 42.

[0042] (3) In Fig. 2, the adder 14 adds the contour component output from the coefficient control unit 17 to the luminance signal Y, which has been input to terminal 16 and delayed for a predetermined time interval by the delay adjusting unit 12, ~~to output~~ and outputs the sum to the output terminal 30 as a contour-emphasized luminance signal.

[0043] For instance, when the luminance level of the luminance signal is [00~1F], contour component (HE/8) is added to the luminance signal Y, and the sum (Y + HE/8) as a contour-emphasized luminance signal is output to the output terminal 30. Further, when the luminance level of the luminance signal Y are [20~3F], [40~7F] or [80~FF], contour component (HE/4), (HE/2) or (HE) is added to the luminance signal Y, and sum (Y + HE/4), (Y + HE/2) or (Y + HE) as a contour-emphasized luminance signal is output to the output terminal 30. Thus, contour emphasis matching the luminance level of luminance signal Y is available.

[0044] The embodiment described above relates to a case where the contour pick-up unit comprises a horizontal contour pick-up unit for sampling the contour component in a horizontal direction from the input video signal, but the present invention is not limited to this embodiment and ~~but~~ is also applicable to other contour pick-up units as long as they are designed to sample the contour component from an input video signal. For example, the present invention is applicable to the case where a contour pick-up unit comprises a vertical contour pick-up unit designed for sampling the contour component

in a vertical direction or to the case where a contour pick-up unit comprises a horizontal-vertical contour pick-up unit designed for sampling the contour component in both the horizontal and vertical directions.

[0045] The embodiment described above relates to a case where the level judging unit comprises a decoder for interpreting whether the luminance level of an input video signal corresponds to ~~which~~ one of four luminance levels, and a coefficient control unit comprises four multipliers for multiplying the contour component sampled by means of the contour pick-up unit by any of coefficients  $1/8$ ,  $1/4$ ,  $1/2$  and  $1$  for the output of respective products, four AND gates respectively connected to the output sides of the four multipliers for using the signal interpreted by the decoder as the gate signal and an OR gate connected to the output sides of the four AND gates, but the present invention is not limited to this embodiment. For example, the present invention is also applicable to a case where the level judging unit comprises a decoder for interpreting whether the luminance level of an ~~a~~-input video signal corresponds to ~~which~~ one of  $n$  number ( $n = 2$  or larger integers) of levels, and the coefficient control unit comprises  $n$  number of multipliers for multiplying the contour component sampled by means of the contour pick-up unit by a corresponding coefficient for outputting the product thereof,  $n$  number of AND gates respectively connected to the output sides of the  $n$  number of multipliers for using, as the gate control signal, the signals interpreted by a decoder, and an OR gate connected to the output sides of the  $n$  number of AND gates.

[0046] The embodiment described above relates to a case where the level judging unit comprises a decoder,

January 6, 2004

and the coefficient control unit comprises multipliers, AND gates and an OR gate, but the present invention is not limited to this embodiment and is ~~but~~ applicable also to the case where the level judging unit may be anything capable of discriminating the luminance level of an input video signal, and the coefficient control unit may be anything capable of selectively changing the coefficient according to the judging signal from the level judging unit, as well as for multiplying the contour component sampled by means of the contour pick-up unit by a corresponding coefficient for the output of the product thereof.

#### INDUSTRIAL APPLICABILITY

[0047] As described in the foregoing, the present invention relates to a contour emphasizing circuit designed for sampling a contour component from an input video signal, multiplying the sampled contour component by a contour emphasizing coefficient, adding the product thereof to the input video signal and outputting a contour-emphasized video signal, whereby the emphasized contour can be ~~emphasized-matching~~ matched with the luminance level of the input video signal. Thus, the present invention can be used ~~for preventing to prevent~~ production of unnatural picture ~~either~~ caused by overemphasizing the contour of a dark picture having a low luminance level by excessively adding a contour component, or by under emphasizing the contour of a bright picture having a high luminance level by adding an insufficient contour component.